

Company name: Created by: Phone:

Date: 6/23/2019

Count | Description

CRN 32-1-1 H-G60-A-V-HQQV



Product No.: 97737700

CR-H pumps are horizontal end suction pumps typically mounted on baseplates.

The end suction design enables the pump to be installed horizontally in traditional, end suction design piping where the pump has an axial suction port and a radial center line discharge port.

This design allows "back pull-out" capability. This means the pump usually can be easily serviced without removing the volute from the pipe system.

CR-H pumps can be selected that meet ASME B73.1 dimensional standards for suction and discharge piping as well as many of the baseplate dimensional standards. CR-H pumps do not fully comply with the ASME B73.1 specification.

Controls:

Frequency converter: NONE Pressure sensor: N

Liquid:

Pumped liquid: Water
Liquid temperature range: -4 .. 194 °F
Selected liquid temperature: 68 °F
Density: 62.29 lb/ft³

Technical:

Rated pump speed: 3457 rpm
Rated flow: 96.9 US gpm
Rated head: 60.37 ft
Pump orientation: Horizontal

End suction pump: Y
Shaft seal arrangement: Single
Code for shaft seal: HQQV
Approvals on nameplate: CURUS

Curve tolerance: ISO9906:2012 3B

Materials:

Base: Stainless steel

EN 1.4408 AISI 316

Impeller: Stainless steel

EN 1.4401 AISI 316 SIC

Bearing: SIC Support bearing: Graflon

Installation:

Maximum ambient temperature: 104 °F Maximum operating pressure: 232.06 psi

Max pressure at stated temperature: 232 psi / 194 °F

232 psi / -4 °F

Size of suction port: 3 inch



Company name: Created by: Phone:

Date: 6/23/2019

Count | Description

Size of outlet port: 2 inch
Pressure rating for pipe connection: PN 16
Flange rating inlet: 150 lb
Flange size for motor: 213TC

Electrical data:

Motor standard: NEMA
Motor type: Baldor
Rated power - P2: 5 HP
Power (P2) required by pump: 5 HP
Main frequency: 60 Hz

Rated voltage: 1 x 208-230 V

Service factor: 1.15
Rated current: 24.0-22.0 A
Rated speed: 3450 rpm

Number of poles: 2 Insulation class (IEC 85): F

Motor Number: 84Z04533

Others:

Net weight: 167 lb Gross weight: 328 lb Shipping volume: 29 ft³ Country of origin: US

Custom tariff no.: 8413.70.2040