

Neo® Trim and Shower Package (Valve not included)

## FEATURES:

- CPT-1001: Shower Valve Trim
- VS-3010: 2.5 GPM (9.5 L/min) Flow Rate Shower Head w/ 60 in. Hose
- VS-155: Supply Ell with Wall Flange
- VS-156: Pause/Trickle Adaptor
- SA-1002: Slide Bar

## VALVE OPTIONS:

- CPV-PB: Pressure Balance Valve  
Sweat & Thread Connections
- CPV-PB-PXC: Pressure Balance Valve  
PEX F1807 Crimp Inlet Connections
- CPV-PB-PXE: Pressure Balance Valve  
PEX F1960 Cold-Expansion Inlet  
Connections
- CPV-T: Thermostatic Valve  
Sweat & Thread Connections
- CPV-T-PXC: Thermostatic Valve  
PEX F1807 Crimp Inlet Connections
- CPV-T-PXE: Thermostatic Valve  
PEX F1960 Cold-Expansion Inlet  
Connections

## STOCK FINISHES:



PC BN

## STANDARDS:

- ASME A112.18.1/CSA B125.1 certified
- ADA compliant

## WARRANTY:


Visit [www.speakman.com](http://www.speakman.com) for full product warranty information

- See [Speakman.com](http://Speakman.com) For Warranty Information




Information continues on next page

## Neo® Trim and Shower Package (Valve not included)



**NOTES:**

1. ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] UNLESS OTHERWISE SPECIFIED AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.
2. ALL INLETS AND OUTLETS ARE 1/2" FEMALE COPPER SWEAT AND 1/2" MALE NPT UNLESS OTHERWISE SPECIFIED.
3. THE LOCATIONS OF THE SLIDE BAR AND SUPPLY ELL ARE OPTIONAL, BUT RESTRICTED BY THE 60" HOSE LENGTH RUNNING FROM THE SUPPLY ELL TO THE HAND SHOWER AND THE 6" MINIMUM REQUIREMENT BETWEEN THE IN-LINE CHECK VALVE AND TOP OF THE HAND SHOWER (WHEN HAND SHOWER IS ADJUSTED TO HIGHEST POSITION).
4. FOR ADA MOUNTING LOCATIONS CONSULT ADAAG, ANSI A117.1, OR STATE REGULATIONS.



| DIMENSION | CPV-PB                                 | CPV-T          | CPV-PB-PXC                              | CPV-PB-PXE       | CPV-T-PXC                                 | CPV-T-PXE      |
|-----------|--|----------------|---|------------------|---|----------------|
| A         | 7/16" (11mm)                           | 1/2" (12mm)    | 7/16" (11mm)                            | 7/16" (11mm)     | 1/2" (12mm)                               | 1/2" (12mm)    |
| B         | 3-5/16" (84mm)                         | 3-1/2" (89mm)  | 3-5/16" (84mm)                          | 3-5/16" (84mm)   | 3-1/2" (89mm)                             | 3-1/2" (89mm)  |
| C         | 4-13/16" (123mm)                       | 5-7/8" (150mm) | 4-13/16" (123mm)                        | 4-13/16" (123mm) | 5-7/8" (150mm)                            | 5-7/8" (150mm) |
| D         | 2-1/2" (63mm) MIN TO 3-1/2" (89mm) MAX |                |   |                  |   |                |
| E         |  |                | 3-1/8" (79mm) MIN TO 4-1/8" (105mm) MAX |                  | 3-3/16" (81mm) MIN TO 4-3/16" (106mm) MAX |                |